



# Radial Agricultural Tire



## LR861 (R-1) Radial Agricultural Tire

Size	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)
320/90R46	146/143	A8/B	W10	3000	320	1744	319

- Better traction and braking performance.
- Better running stability.
- Save work time and fuel.
- Suitable for modern mechanical equipment.



## LR861 (R-1W) Radial Agricultural Tire

Size	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)
280/85R24	115/112	A8/B	W3	1215	160	1086	282
320/85R24	122/119	A8/B	W10	1500	160	1154	319
320/85R28	124/121	A8/B	W10	1600	160	1255	319
320/85R32	126/123	A8/B	W10	1700	160	1357	319
320/85R32	142/139	A8/B	W10	2650	400	1357	319
320/85R36	128/125	A8/B	W10	1800	160	1458	319
340/85R24	125/122	A8/B	W11	1650	160	1188	343
340/85R28	127/124	A8/B	W11	1750	160	1289	343
340/85R32	142/139	A8/B	W11	2650	360	1391	343
340/85R38	133/130	A8/B	W11	2060	160	1543	343
380/85R24	131/128	A8/B	W12	1950	160	1256	380
380/85R28	133/130	A8/B	W12	2060	160	1357	380
380/85R30	135/132	A8/B	W12	2180	160	1408	380
380/85R34	137/137	A8/B	W12	2300	160	1510	380
380/85R34	147/147	A8/B	W12	3075	240	1510	380
420/85R24	137/134	A8/B	W13	2300	160	1324	418
420/85R28	139/136	A8/B	W13	2430	160	1425	418
420/85R30	140/137	A8/B	W13	2500	160	1476	418
420/85R34	142/139	A8/B	W13	2650	160	1578	418
420/85R38	144/141	A8/B	W13	2800	160	1679	418
460/85R30	145/142	A8/B	W14L	2900	160	1544	455
460/85R34	147/144	A8/B	W14L	3075	160	1646	455
460/85R38	149/146	A8/B	W14L	3250	160	1747	455
460/85R42	150/147	A8/B	W14L	3350	160	1849	455
520/85R38	155/152	A8/B	DW16L	3875	160	1849	516
520/85R42	157/154	A8/B	DW16L	4125	160	1951	516
480/80R46	145/142	A8/B	W13A	2900	160	1840	418
480/80R42	151/151	A8/B	DW16L	3450	160	1835	479
480/80R42	156/156	A8/B	DW16L	4000	240	1835	479
480/80R46	152/149	A8/B	DW16L	3550	160	1936	479
480/80R46	158/158	A8/B	DW16L	4250	240	1936	479
380/90R46	149/149	A8/B	W12	3250	240	1852	380
380/90R46	157/157	A8/B	W12	4125	358	1852	380
420/90R30	142/139	A8/B	W13	2650	160	1518	418
420/90R30	147/144	A8/B	W13	3075	240	1518	418

- Better traction and braking performance.
- Better running stability.
- Save work time and fuel.
- Suitable for modern mechanical equipment.



## LR650 (R-1W)

Radial Agricultural Tire



## LR700 (R-1W)

Radial Agricultural Tire

Size	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)
440/65R24	128/131	D/A8	W14L	1800	160	1182	441
440/65R28	131/134	D/A8	W14L	1950	160	1283	441
480/65R24	133/136	D/A8	W15L	2060	160	1234	479
480/65R28	136/139	D/A8	W15L	2240	160	1335	479
540/65R24	140/143	D/A8	W18L	2500	160	1312	550
540/65R28	142/145	D/A8	W18L	2650	160	1413	550
540/65R30	150/153	D/A8	W18L	3350	240	1464	550
540/65R34	145/148	D/A8	W18L	2900	160	1566	550
600/65R28	147/150	D/A8	W18L	3075	160	1491	591
600/65R38	153/156	D/A8	W18L	3650	160	1745	591
650/65R38	157/160(trial)	D/A8	DW20B	4125	160	1811	645
650/65R42	165/168(trial)	D/A8	DW20B	4250	240	1913	645
710/70R38	166/169	D/A8	DW23B	5300	160	1959	716
710/70R42	168/171	D/A8	DW23B	5600	160	2061	716

- Longer service life.
- Excellent stability and comfort.
- More efficient traction.
- Outstanding floating behavior reduces pressure to land.

Size	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)
360/70R24	122/119	A8/B	W11	1500	160	1152	357
360/70R24	127/124	A8/B	W11	1750	240	1152	357
420/70R24	130/127	A8/B	W13	1900	160	1248	418
420/70R24	136/133	A8/B	W13	2240	240	1248	418
420/70R28	139/136	A8/B	W13	2430	240	1349	418
480/70R24	138/135	A8/B	W15L	2360	160	1316	479
480/70R28	140/137	A8/B	W15L	2500	160	1421	479
480/70R28	145/142	A8/B	W15L	2900	240	1421	479
480/70R28	151/148	A8/B	W15L	3450	320	1421	479
480/70R34	143/143	A8/B	W15L	2725	160	1580	479
480/70R38	145/142	A8/B	W15L	2900	160	1681	479
580/70R38	155/155	A8/B	W13L	3875	160	1827	577
580/70R38	170/167	A8/B	W13L	6000	280	1827	577

- Savings in time and fuel.
- Better self-cleaning capability.
- Comfort on the road and in the field.



# Radial OTR



## LB03SD (L-5)

Radial OTR

Size	Ply Rating	Load Index		Rim	10km/h		50km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		Load (kg)	Inflated Pressure (kPa)	Load (kg)	Inflated Pressure (kPa)			
		17.5R25	☆☆		167	182	14.00/1.5	8500			
20.5R25	☆☆	177	193	17.00/2.0	11500	575	730	450	1548	520	72
23.5R25	☆☆	185	201	19.5/2.5	14500	575	925	450	1673	597	78.5
26.5R25	☆☆	193	209	22.00/3.0	18500	575	11500	450	1798	673	87.5
29.5R25	☆☆	200	216	25.00/3.5	22400	575	14000	450	1921	750	95

- A substantial crown, robust shoulders reinforced with a protection band make up a tyre particularly resistant to shock ruptures, cuts and tread tearing.
- A very substantial, wide and aggressive tread functions perfectly to produce a good compromise between adhesion, traction and damage resistance.



## LB02SD (L-5)

Radial OTR

Size	Ply Rating	Load Index		Rim	10km/h		50km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		Load (kg)	Inflated Pressure (kPa)	Load (kg)	Inflated Pressure (kPa)			
		20.5R25	☆☆		177	193	17.00/2.0	11500			
23.5R25	☆☆	185	201	19.5/2.5	14500	575	925	450	1673	597	78.5
26.5R25	☆☆	193	209	22.00/3.0	18500	575	11500	450	1798	673	87.5
29.5R25	☆☆	200	216	25.00/3.5	22400	575	14000	450	1921	750	95

- Massive tread blocks characterise this tyre.
- The extra deep tread pattern (L5) of this tyre gives outstanding wear life potential.
- The sidewall/tread intersection design gives an excellent level of damage and cut resistance.
- A wide, square tread gives better stability in loading operations and whilst travelling.



## LMS401 (E-4)

Radial OTR

Size	Ply Rating	Load Index		Rim	10km/h		50km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		Load (kg)	Inflated Pressure (kPa)	Load (kg)	Inflated Pressure (kPa)			
		29.5R25	☆☆		200	216	25.00/3.5	22400			

- Massive tread blocks characterise this tyre, it delivers excellent tractive performance, better lateral adhesion and more efficient loading for machines working at the face.
- Flower chime angle changed design, it delivers good self-cleaning.
- A wide, square tread gives better stability in loading operations and whilst travelling.



## LLA28

Radial OTR

Size	Ply Rating	Load Index		Rim	10km/h		50km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		Load (kg)	Inflated Pressure (kPa)	Load (kg)	Inflated Pressure (kPa)			
		16.00R25	☆☆		177	195	11.25/2.0	12150			

- The tire is designed to guarantee the best comfort for the operator, a smooth and silent ride in the high speed transfer, excellent traction on all surfaces.
- Open shoulder pattern can effectively reduce tire temperature.



## LB01N (E-3/L-3/G-3)

Radial OTR

Size	Ply Rating	Load Index		Rim	10km/h		50km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		Load (kg)	Inflated Pressure (kPa)	Load (kg)	Inflated Pressure (kPa)			
		17.5R25	☆☆		167	182	14.00/1.5	8500			
20.5R25	☆☆	177	193	17.00/2.0	11500	575	7300	450	1492	520	31.0
23.5R25	☆☆	185	201	19.5/2.5	14500	575	9250	450	1617	597	34.0
26.5R25	☆☆	193	209	22.00/3.0	18500	575	11500	450	1750	673	37.0
29.5R25	☆☆	200	216	25.00/3.5	22400	575	14000	450	1873	750	40.0

- Exceptional traction and manoeuvrability.
- Good flotation.
- Excellent stability and comfort.



## LM01N (E-3/L-3)

Radial OTR

Size	Ply Rating	Load Index		Rim	10km/h		50km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		Load (kg)	Inflated Pressure (kPa)	Load (kg)	Inflated Pressure (kPa)			
		23.5R25	☆☆		185	201	19.5/2.5	14500			

- Exceptional traction and manoeuvrability.
- Good flotation.
- Excellent stability and comfort.



## LM11N (E-3/L-3)

Radial OTR

Size	Ply Rating	Load Index		Rim	70km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	
		70km/h Speed Symbol E			Load	Inflated Pressure				
					(kg)	(kPa)				
445/95R25	☆☆	177		11.25/2.0		7300	900	1431	435	24.0
385/95R25	☆☆	170		10.00/1.5		6000	900	1339	379	22.0

- Exceptional traction and manoeuvrability.
- Good flotation.
- Excellent stability and comfort.



## LB02S (E-4/L-4)

Radial OTR

Size	Ply Rating	Load Index		Rim	10km/h		50km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		Load	Inflated Pressure	Load	Inflated Pressure				
					(kg)	(kPa)	(kg)	(kPa)				
18.00R33	☆☆	191	209	13.00/2.5		18500	800	10900	650	1877	498	54.0

- Exceptional traction and manoeuvrability.
- Good flotation.
- Excellent stability and comfort.



## LB03S (E-4/L-4)

Radial OTR

Size	Ply Rating	Load Index		Rim	10km/h		50km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		Load	Inflated Pressure	Load	Inflated Pressure				
					(kg)	(kPa)	(kg)	(kPa)				
16.00R25	☆☆	177	195	11.25/2.0		12150	800	7300	650	1548	432	43.0
18.00R25	☆☆	185	204	13.00/2.5		16000	800	9250	650	1673	498	47.0

- High safety.
- Wide contact area with ground provides strong grip.
- Low noise.



## LB06S (E-3/L-3)

Size	Ply Rating	Load Index		Rim	10km/h		50km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		Load	Inflated Pressure	Load	Inflated Pressure				
					(kg)	(kPa)	(kg)	(kPa)				
750/65R25	☆☆	190	/	24.00/3.0	/	/	/	10600	425	1610	754	46.0
29.5R25	☆☆	200	216	25.00/3.5		22400	575	14000	450	1921	750	45.0

- Good traction and wear resistance.
- Excellent tear resistance.



## DM992

High Tear Resistance

Size	Ply Rating	Load Index		Rim	10km/h		50km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	
		TRANSP 65km/h Speed Symbol D	LOADING 10km/h Speed Symbol A2		Load	Inflated Pressure	Load	Inflated Pressure				
					(kg)	(kPa)	(kg)	(kPa)				
14.00R25	☆☆☆	169	188	10.00/1.5		10000	950	5800	700	1370	375	25.0

- Long life.
- Excellent adhesion and traction in bad conditions.



## D990

High Tear Resistance

Size	Ply Rating	Load Index		Rim	80km/h		Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	
		80km/h Speed Symbol F			Load (Single/Dual)	Inflated Pressure (Single/Dual)				
					(kg)	(kPa)				
16.00R20	22	174/171		11.25		6700/6150	760	438	1320	20.5

- Good traction and wear resistance.
- Excellent tear resistance.