



# Bias Truck / Bus Tire



**LL1**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
12.00-24	16	156/132	G	8.5	D3550 S4000	670/740	1225	315	15.0
12.00-24	18	158/134	G	8.5	D3750 S4250	740/810	1225	315	15.0

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.



**LL2**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.00-16LT	10	111/106	K	5.50F	D950 S1090	530	775	200	12.0
7.00-16LT	12	115/110	K	5.50F	D1060 S1215	530	775	200	12.0
7.00-16LT	14	118/114	K	5.50F	D1180 S1320	730	775	200	12.0
9.00-20	12	138/133	G	7.0	D2060 S2360	600/670	1018	259	15.0
9.00-20	14	141/137	G/K	7.0	D2300 S2575	700/770	1018	259	15.0
9.00-20	16	145/140	G	7.0	D2500 S2900	810/880	1018	259	15.0
10.00-20	16	146/142	G	7.5	D2650 S3000	740/810	1055	278	15.0
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1055	278	15.0
12.00-20	16	152/148	G	8.5	D3150 S3550	670/740	1125	315	15.0
12.00-20	18	154/150	G	8.5	D3350 S3750	740/810	1125	315	15.0

- Good wear and crack resistance.
- High traction.



**LL3**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
8.25-20	10	129/124	G	6.5	D1600 S1850	530/600	974	236	15.0
8.25-20	14	136/131	G	6.5	D1950 S2240	740/810	974	236	15.0

- Wear and crack resistance.
- Lateral grip.
- Good heat dissipation.



**LL4**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
9.00-20	12	138/133	G	7.0	D2060 S2360	600/670	1018	259	15.0
9.00-20	14	141/137	G/K	7.0	D2300 S2575	700/770	1018	259	15.0
9.00-20	16	145/140	G	7.0	D2500 S2900	810/880	1018	259	15.0
11.00-20	16	150/145	G	8.0	D2900 S3350	740/810	1085	293	16.0
11.00-20	18	153/148	G	8.0	D3150 S3650	840/910	1085	293	16.0

- Good wear and crack resistance.



**LL6**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
9.00-20	12	138/133	G	7.0	D2060 S2360	600/670	1018	259	15.0
9.00-20	14	141/137	G	7.0	D2300 S2575	700/770	1018	259	15.0
9.00-20	16	145/140	G	7.0	D2500 S2900	810/880	1018	259	15.0
12.00-24	16	156/132	G	8.5	D3550 S4000	670/740	1225	315	16.0
12.00-24	18	158/154	G	8.5	D3750 S4250	740/810	1225	315	16.0

- Good wear and crack resistance.
- High traction.



**LL7**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50-20	12	128/124	G	6.0	D1600 S1800	670/740	935	215	14.0
7.50-20	14	130/126	G	6.0	D1700 S1900	740/810	935	215	14.0

- Good wear and crack resistance.
- Lateral grip.



**LL8**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.00-15LT	10	109/105	K	5.50F	D925 S1030	630	750	200	10.0
7.00-15LT	12	113/109	K	5.50F	D1030 S1150	630	750	200	10.0
7.50-15LT	12	119/115	K	6.00G	D1215 S1360	630	780	215	11.0
7.00-20	10	121/117	G	5.5	D1285 S1450	560/630	904	200	12.0
7.00-20	12	124/120	G	5.5	D1400 S1600	670/740	904	200	12.0

- Good wear and crack resistance.
- High traction.



**LL47**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.00-20	10	121/117	G	5.5	D1285 S1450	560/630	904	200	12.0
7.00-20	12	124/120	G	5.5	D1400 S1600	670/740	904	200	12.0
7.00-20	14	127/123	G	5.5	D1550 S1750	770/840	904	200	12.0
8.25-20	14	136/131	G/K	6.5	D1950 S2240	740/810	974	236	14.0
8.25-16LT	14	126/122	K/L	6.50H	D1500 S1700	630	855	235	12.5
8.25-16LT	16	128/124	K/L	6.50H	D1600 S1800	730	855	235	12.5
9.00-20	14	141/137	G/K	7.0	D2300 S2575	700/770	1018	259	15.0
9.00-20	16	145/140	G	7.0	D2500 S2900	810/880	1018	259	15.0
10.00-20	16	146/142	G	7.5	D2650 S3000	740/810	1055	278	15.0
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1055	278	15.0
11.00-20	16	150/145	G	8.0	D2900 S3350	740/810	1085	293	15.0
11.00-20	18	153/148	G	8.0	D3150 S3650	840/910	1085	293	15.0
12.00-20	16	152/148	G	8.5	D3150 S3550	670/740	1125	315	15.0
12.00-20	18	154/150	G	8.5	D3350 S3750	740/810	1125	315	15.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



**LL48**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
9.00-20	12	138/133	G	7.0	D2060 S2360	600/670	1018	259	13.5
9.00-20	14	141/137	G	7.0	D2300 S2575	700/770	1018	259	13.5
9.00-20	16	145/140	G	7.0	D2500 S2900	810/880	1018	259	13.5

- Fuel saving.
- Low noise.
- Wear resistance.
- Good heat dissipation.



**LL57**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10.00-20	16	146/142	G	7.5	D2650 S3000	740/810	1055	278	16.0
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1055	278	16.0

- Good heat dissipation.
- Multiple functions.
- Crack resistance.



**LL58**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10.00-20	16	146/142	G	7.5	D2650 S3000	740/810	1055	278	16.0
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1055	278	16.0

- Shell strength,available for more heavy load.



## LL59

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50-16LT	14	122/118	K	6.00G	D1320 S1500	730	805	215	12.0
7.50-16LT	16	126/123	K	6.00G	D1520 S1700	850	805	215	12.0
8.25-16LT	14	126/122	K	6.50H	D1500 S1700	630	835	235	14.5
8.25-16LT	16	128/124	K	6.50H	D1600 S1800	730	835	235	14.5
9.00-20	14	141/137	G	7.0	D2300 S2575	700/770	1018	259	14.0
9.00-20	16	145/140	G	7.0	D2500 S2900	810/880	1018	259	14.0
10.00-20	16	146/142	G	7.5	D2650 S3000	740/810	1055	278	14.0
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1055	278	14.0
11.00-20	16	150/145	G	8.0	D2900 S3350	740/810	1085	293	15.0
11.00-20	18	153/148	G	8.0	D3150 S3650	840/910	1085	293	15.0
12.00-20	16	152/148	G	8.5	D3150 S3550	670/740	1125	315	15.0
12.00-20	18	154/150	G	8.5	D3350 S3750	740/810	1125	315	15.0
12.00-20	20	156/151	G	8.5	D3450 S4000	810/880	1125	315	15.0
14.00-20	18	161/156	E	10.0	D4000 S4625	600/670	1240	375	20.0
14.00-20	20	164/159	E	10.0	D4375 S5000	700/770	1240	375	20.0

- Available for heavy load.
- Good wear resistance.
- Stable performance.



## LL61

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50-20	12	128/124	G	6.0	D1600 S1800	670/740	935	215	11.5
7.50-20	14	130/126	G	6.0	D1700 S1900	740/810	935	215	11.5

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



## LL67

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.00-15	8	105/101	L	5.50F	D825 S925	410	750	200	8.5
7.50-16	10	116/112	L	6.00G	D1120 S1250	520	805	215	8.0
10.00-20	14	144/139	G	7.5	D2430 S2800	D620 S690	1055	278	11.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



## LL68

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
12.00-20	18	154/150	G	8.5	D3350 S3750	740/810	1145	315	15.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



## LL78

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
12.00-18	12	/	/	9.00V	1800	350	1090	327	14.0

- Lateral grip and wear resistance.
- Good traction.



**LL77**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1073	278	20.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



**LL79**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
8.25-20	14	136/131	G	6.5	D1950 S2240	740/810	974	236	13.5

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



**LL87**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50-16LT	14	122/118	K	6.00G	D1320 S1500	730	816	215	17.5
8.25-16LT	14	126/122	K	6.50H	D1500 S1700	630	855	235	14.0
8.25-20	14	136/131	G	6.5	D1950 S2240	740/810	974	236	14.0
9.00-20	16	145/140	G	7.0	D2500 S2900	810/880	1018	259	15.0
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1073	278	20.0
11.00-20	18	153/148	G	8.0	D3150 S3650	840/910	1085	293	16.0
12.00-20	18	154/150	G	8.5	D3350 S3750	740/810	1125	315	16.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



**LL88**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10.00-20	16	146/142	G	7.5	D2650 S3000	740/810	1073	278	16.5
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1073	278	16.5
11.00-20	18	153/148	G	8.0	D3150 S3650	840/910	1085	293	16.5

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



**LL95**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
13.00-20	16	156/151	E	9.0	D3450 S3875	600/670	1177	340	18.0
13.00-20	18	158/154	E	9.0	D3750 S4250	700/770	1177	340	18.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



**LL96**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1073	278	20.0
11.00-20	16	150/145	G	8.0	D2900 S3350	740/810	1105	293	21.0
11.00-20	18	153/148	G	8.0	D3150 S3650	840/910	1105	293	21.0
12.00-20	18	154/150	G	8.5	D3350 S3750	740/810	1145	315	21.0
14.00-20	20	164/159	E	10.0	D4375 S5000	700/770	1265	375	22.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



**LL96-T**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.00-16LT	14	118/114	G	5.50F	D1180 S1320	730	785	200	20.0
7.50-16LT	14	122/118	G	5.00G	D1320 S1500	730	816	215	22.0
7.50-16LT	16	126/123	G	5.00G	D1520 S1700	850	816	215	22.0
8.25-16LT	14	126/122	G	5.50H	D1500 S1700	630	867	235	22.0
8.25-16LT	16	128/124	G	5.50H	D1600 S1800	730	867	235	22.0
8.25-20	14	136/131	C	6.5	D1950 S2240	740/810	992	236	19.0
9.00-20	16	145/140	B	7.0	D2500 S2900	840/880	1038	259	22.0
11.00-20	18	153/148	C	8.0	D3150 S3650	840/910	1105	293	25.0
12.00-20	18	154/150	C	8.5	D3350 S3750	740/810	1145	315	25.0
13.00-20	18	158/154	B	9.0	D3750 S4250	700/770	1200	340	24.0

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.



**SL96-T**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10.00-20	18	150/145	C	7.5	D2900 S3350	840/910	1073	278	25.0

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.



## LL97

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
9.00-20	16	145/140	G	7.0	D2500 S2900	810/880	1018	259	15.0
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1073	278	20.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



## LL99

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50-16LT	16	126/123	K	6.00G	D1520 S1700	650	816	215	16.0
8.25-16LT	16	128/124	K	6.50H	D1600 S1800	730	867	235	16.5
9.00-16LT	16	134/129	K	6.50H	D1850 S2120	730	902	255	17.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



## LL98

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
9.00-20	16	145/140	G	7.0	D2500 S2900	810/880	1038	259	20.0
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1073	278	21.0
12.00-20	18	154/150	G	8.5	D3350 S3750	740/810	1145	315	21.0
14.00-20	20	164/159	E	10.0	D4375 S5000	700/770	1265	375	22.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



## SL106

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1055	278	15.5

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.



**SL108**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
9.00-20	16	145/140	G	7.0	D2500 S2900	810/880	1018	259	15.0
10.00-20	16	146/142	G	7.5	D2650 S3000	740/810	1055	278	15.5
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1055	278	15.5
11.00-20	16	150/145	G	8.0	D2900 S3350	740/810	1085	293	15.5
11.00-20	18	153/148	G	8.0	D3150 S3650	840/910	1085	293	15.5
12.00-20	18	154/150	G	8.5	D3350 S3750	740/810	1125	315	16.0

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.



**LL109**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.00-16LT	12	113/109	K	5.50F	D1030 S1150	630	760	200	15.0
7.50-16LT	14	122/118	K	6.00G	D1320 S1500	730	816	215	14.5
8.25-16LT	16	128/124	K	6.50H	D1600 S1800	730	867	235	16.5
8.25-20	14	136/131	G	6.5	D1950 S2240	740/810	974	236	14.0
11.00-20	18	153/148	G	8.0	D3150 S3650	840/910	1085	293	16.0

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.



**LL147**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10.00-20	18	150/145	G	7.5	D2900 S3350	840/910	1073	278	17.0

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.



**LL150**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
14.00-20	20	164/159	E	10.0	D4375 S5000	700/770	1265	375	26.0

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.



**LL158**  
Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
9.00-20	14	141/137	B	7.00T	D2300 S2575	700/770	1038	259	20.0

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.





## LL159

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.50-16LT	10	107/103	K	5.50F	D875 S975	530	750	185	10.0
7.50-16LT	12	120/116	K	6.00G	D1250 S1400	630	805	215	12.0
7.50-20	14	130/126	G	6.0	D1700 S1900	740/810	935	215	12.0
8.25-16LT	14	126/122	K	6.50H	D1500 S1700	630	855	235	13.5
8.25-20	14	136/131	G	6.5	D1950 S2240	740/810	974	236	13.5
10.00-20	16	146/142	G	7.5	D2650 S3000	740/810	1055	278	14.5
11.00-20	18	153/148	G	8.0	D3150 S3650	840/910	1085	293	15.0
12.00-20	18	154/150	G	8.5	D3350 S3750	740/810	1125	315	15.0

- Available for heavy load.
- Good wear resistance.
- Stable performance.



## LL178

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.50-16LT	10	107/103	K	5.50F	D875 S975	530	750	185	10.0
7.00-16LT	10	111/116	K	5.50F	D950 S1090	530	775	200	11.5
7.00-16LT	12	115/110	K/L	5.50F	D1060 S1215	630	775	200	11.5
7.50-16LT	12	120/116	K	6.00G	D1250 S1400	630	805	215	11.5
7.50-20	14	130/126	G	6.0	D1700 S1900	740/810	935	215	11.5
8.25-16LT	14	126/122	K	6.50H	D1500 S1700	630	855	235	12.0
8.25-20	14	136/131	G	6.5	D1950 S2240	740/810	974	236	13.0

- Available for heavy load.
- Good wear resistance.
- Stable performance.



## LL168

Bias Truck/Bus Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.50-16LT	10	107/103	K	5.50F	D875 S975	530	750	185	10.0
7.00-16LT	12	115/110	K/L	5.50F	D1060 S1215	630	775	200	11.5
7.50-16LT	12	120/116	K	6.00G	D1250 S1400	630	805	215	11.5
7.50-20	14	130/126	G K	6.0	D1700 S1900	740/810	935	215	11.5
8.25-16LT	14	126/122	K/L	6.50H	D1500 S1700	630	855	235	12.0
8.25-16LT	16	128/124	K/L	6.50H	D1600 S1800	730	855	235	12.0
8.25-20	14	136/131	G K	6.5	D1950 S2240	740/810	974	236	14.0
9.00-20	14	141/137	G K	7.0	D2300 S2575	700/770	1018	259	14.0
9.00-20	16	145/140	G	7.0	D2500 S2900	810/880	1018	259	14.0
10.00-20	16	146/142	G	7.5	D2650 S3000	740/810	1055	278	14.0
11.00-20	16	150/145	G	8.0	D2900 S3350	740/810	1085	293	15.0
11.00-20	18	153/148	G	8.0	D3150 S3650	840/910	1085	293	15.0
12.00-20	18	154/150	G	8.5	D3350 S3750	740/810	1125	315	15.0

- Available for heavy load.
- Good wear resistance.
- Stable performance.



## LL180

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
8.25-20	14	136/131	G	6.5	D1950 S2240	740/810	974	236	13.5
12.00-24	18	158/154	G	8.5	D3750 S4250	740/810	1225	315	17.0

- Available for long-distance transport.
- Strong loading capacity and high speed performance.
- Strong resistance to wear and puncture.



# Bias Light Truck Tire



**MG-99**  
Bias Light Truck Tire



Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50-16LT	16	126/123	K	6.00G	D1520 S1700	850	816	215	18.0

- Wear and crack resistance.
- Lateral grip.



**LL9**  
Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.00-15LT	8	97/92	K	4.50E	D630 S730	420	705	170	9.0
6.00-15LT	10	101/97	K/L	4.50E	D730 S825	530	705	170	9.0
6.50-15LT	8	101/97	K/L	4.50E	D730 S825	420	730	180	9.0
6.50-15LT	10	106/101	K/L	4.50E	D825 S950	530	730	180	9.0
7.50-15LT	10	115/110	K	6.00G	D1060 S1215	530	780	215	11.0
7.50-15LT	12	119/115	K/L	6.00G	D1215 S1360	630	780	215	11.0
7.50-16LT	10	116/112	K/L	6.00G	D1120 S1250	530	805	215	11.5
7.50-16LT	12	120/116	K/L	6.00G	D1250 S1400	630	805	215	11.5
7.50-16LT	14	122/118	K/L	6.00G	D1320 S1500	730	805	215	11.5
7.50-16LT	16	126/123	K	6.00G	D1520 S1700	850	805	215	11.5

- Low noise.
- Low rolling resistance.
- Good heat dissipation.



**LL10**  
Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50-16LT	8	112/107	K/L	6.00G	D975 S1120	420	805	215	13.0
7.50-16LT	10	116/112	K	6.00G	D1120 S1250	530	805	215	13.0

- Good side slip resistance and braking property.



**LL11**  
Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.50-16LT	8	102/98	K	5.50F	D750 S850	420	750	185	10.0
6.50-16LT	10	107/103	K/L	5.50F	D875 S975	530	750	185	10.0
6.50-16LT	12	110/105	K/L	5.50F	D925 S1060	630	750	185	10.0
7.00-15LT	10	109/105	K/L	5.50F	D925 S1030	530	750	200	10.0
7.00-15LT	12	113/109	K	5.50F	D1030 S1150	630	750	200	10.0
7.00-16LT	8	107/102	K	5.50F	D850 S975	420	775	200	12.0
7.00-16LT	10	111/106	K/L	5.50F	D950 S1090	530	775	200	12.0
7.00-16LT	12	115/110	K/L	5.50F	D1060 S1215	630	775	200	12.0
7.00-16LT	14	118/114	K	5.50F	D1180 S1320	730	775	200	12.0

- Low noise and fuel saving.
- Good wear resistance and heat dissipation.



**LL14**  
Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.50-16LT	8	102/98	K	5.50F	D750 S850	420	750	185	10.5
6.50-16LT	10	107/103	K	5.50F	D875 S975	530	750	185	10.5
6.50-16LT	12	110/105	K	5.50F	D925 S1060	630	750	185	10.5

- Low rolling resistance.
- Good wear and crack resistance.
- Multiple functions.



**LL15**  
Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.00-13LT	6	88/83	K	4.50B	D487 S560	320	655	170	9.0
6.00-13LT	8	93/89	K	4.50B	D580 S650	420	655	170	9.0
6.00-14LT	8	95/90	K	4 1/2J	D600 S690	420	680	170	9.0
6.00-14LT	10	99/95	K	4 1/2J	D710 S800	530	680	170	9.0
6.00-15LT	8	97/92	K	4.50E	D630 S730	420	705	170	9.0
6.00-15LT	10	101/97	K	4.50E	D730 S825	530	705	170	9.0
6.50-14LT	8	99/95	K	4 1/2J	D690 S775	420	705	180	9.0
6.50-14LT	10	104/100	K	4 1/2J	D800 S900	530	705	180	9.0
6.50-15LT	8	101/97	K	4.50E	D730 S825	420	730	180	9.0
6.50-15LT	10	106/101	K/L	4.50E	D825 S950	530	730	180	9.0
6.50-16LT	10	107/103	K/L	5.50F	D875 S975	530	750	185	10.0
6.50-16LT	12	110/105	K	5.50F	D925 S1060	630	750	185	10.0
7.50-16LT	10	116/112	K/L	6.00G	D1120 S1250	530	805	215	13.0
7.50-16LT	12	120/116	K	6.00G	D1250 S1400	630	805	215	13.0
7.50-16LT	14	122/118	K	6.00G	D1320 S1500	730	805	215	13.0
7.50-16LT	16	126/123	K	6.00G	D1520 S1700	850	805	215	13.0
8.25-16LT	14	126/122	K	5.50H	D1500 S1700	630	855	235	14.5
8.25-16LT	16	128/124	K	5.50H	D1600 S1800	730	855	235	14.5

- Good wear and crack resistance.



**LL16**  
Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.50-14LT	8	99/92	K/L	4 1/2J	D690 S775	420	750	180	9.0
6.50-14LT	10	104/100	K/L	4 1/2J	D800 S900	530	750	180	9.0

- Good wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



**LL17**  
Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.00-14LT	8	95/90	K	4 1/2J	D600 S690	420	680	170	9.0
6.00-14LT	10	100/96	K	4 1/2J	D710 S800	530	680	170	9.0

- Good wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.
- Lateral grip.



**LL19**  
Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.50-13LT	8	88/84	K	4.00B	D500 S560	420	620	160	9.0

- Good wear resistance.
- Low noise.
- Good heat dissipation.
- Fuel saving.



**LL18**  
Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.00-13LT	6	88/83	K	4.50B	D487 S560	320	655	170	9.0
6.00-13LT	8	93/89	K/L	4.50B	D580 S650	420	655	170	9.0

- Good wear and crack resistance.
- Fuel saving.
- Good heat dissipation.



**LL62**  
Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50-16LT	14	122/118	K	3.00G	D1320 S1500	730	816	215	16.0
7.50-16LT	16	126/123	K	3.00G	D1520 S1700	350	816	215	16.0

- Wear and crack resistance.
- Lateral grip.



## LL89

Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50-16LT	14	122/118	K	6.00G	D1320 S1500	730	816	215	15.5
7.50-16LT	16	124/120	K	6.00G	D1390 S1580	758	816	215	15.5
8.25-16LT	16	128/124	K	6.50H	D1600 S1800	730	867	235	18.5

- Wear and crack resistance.
- Lateral grip.



## LL201

Bias Light Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.50-16LT	10	107/103	K	5.50F	D875 S975	530	750	185	10.0
7.00-16LT	12	115/110	K	5.50F	D1060 S1215	630	775	200	12.0
7.50-16LT	8	112/107	K/L	6.00G	D975 S1120	410	816	215	12.0
7.50-16LT	10	116/112	K/L	6.00G	D1120 S1250	520	816	215	12.0

- Good wear resistance.
- Good heat dissipation.
- Low noise.
- Fuel saving.



# Bias Mini Truck Tire



## LL20

Bias Mini Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.00-10ULT	8	79/77	K	3.50B	D412 S437	200	517	143	8.0
5.00-12ULT	6	78/76	K	3.50B	D400 S425	200	568	143	8.0
5.00-12ULT	8	83/81	K	3.50B	D462 S487	200	568	143	8.0
5.00-12ULT	10	88/86	K	3.50B	D530 S560	200	568	143	8.0

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.
- Low noise.



**LL21**  
Bias Mini Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.50-12ULT	8	77/76	K	3.00B	D400 S412	400	545	127	7.0

- Good wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.
- Low noise.



**LL41**  
Bias Mini Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.00-12ULT	6	78/76	K	3.50B	D400 S425	300	568	143	8.0
5.00-12ULT	8	83/81	K	3.50B	D462 S487	400	568	143	8.0
5.00-12ULT	10	88/86	K	3.50B	D530 S560	500	568	143	8.0
5.50-12ULT	10	92/89	K	4J	620	530	594	160	8.0

- Good wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.
- Low noise.



**LL51**  
Bias Mini Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.00-12ULT	8	83/81	K	3.50B	D462 S487	400	568	143	8.0

- Good wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



**LL75**  
Bias Mini Truck Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.50-10ULT	6	60/57	K	3.50D	D230 S250	300	470	120	7.0
4.50-10ULT	8	72/70	K	3.50D	D335 S350	400	470	120	7.0

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.
- Low noise.



**LL24**  
Bias Passenger Car Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.00-12	6	73	K	4.50B	360	210	574	156	7.0
6.00-12	8	76	K	4.50B	400	250	574	156	7.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.

# Bias Passenger Car Tire



**LL19**  
Bias Passenger Car Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.60-13	4	70	K	4J	330	170	600	145	6.0
5.60-13	6	74	K	4J	370	210	600	145	6.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



**LL64**  
Bias Passenger Car Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.90-13	4	73	K	4J	370	170	616	150	8.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



## LL80

Bias Passenger Car Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.90-13	4	73	K	4J	370	170	616	150	9.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



## LL117

Temporary-use Spare Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
T155/90D16	/	110	M	4T	1060	420	686	152	3.8

- Low rolling resistance.
- Good heat dissipation.



## OTR Tire



## LD701

OTR Tire



Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
18-20	14	/	/	4.00T	4625	360	1090	455	16.0
20-20	16	/	/	4.00T	6000	360	1180	505	17.0
22-20	14	/	/	17.0	4125	280	1075	555	18.0

- Available for gravel road.
- Good delivery performance.
- Low rolling resistance and good heat dissipation.
- Lateral grip.





## LP401(E-4)

OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
14.00-24	24	/	/	10.0	9500	850	1420	375	65.0
14.00-24	28	/	/	10.0	10000	925	1420	375	65.0
14.00-24	32	/	/	10.0	10900	1050	1420	375	65.0
14.00-24	36	/	/	10.0	16200	1100	1420	375	65.0
18.00-25	32	/	/	13.00/2.5	15000	750	1675	500	72.0
18.00-25	36	/	/	13.00/2.5	16000	850	1675	500	72.0
18.00-25	40	/	/	13.00/2.5	17000	950	1675	500	72.0
18.00-25	44	/	/	13.00/2.5	18000	1050	1675	500	72.0
18.00-25	48	/	/	13.00/2.5	27600	1100	1675	500	72.0

- Extra deep tread pattern ensure tyre life.
- Wider tread blocks enhance traction performance.
- Special compound design for ports, low heat-generation, excellent wear and tear resistance.



## LL26 (E-3)

OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
18.00-25	32	/	/	13.00/2.5	8750	575	1615	500	30.0
18.00-25	40	/	/	13.00/2.5	9750	700	1615	500	30.0

- Available for mobile cranes.
- Stable driving and high loading property.



## LL25 (E-3/L-3)

OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
15.5-25	12	/	/	12.00/1.3	5600	400	1275	395	25.0
16.00-25	28	/	/	1.25/2.0	6700	575	1495	430	28.5
16.00-25	32	/	/	1.25/2.0	7300	650	1495	430	28.5
17.5-25	12	/	/	14.00/1.5	6150	350	1350	445	25.5
17.5-25	16	/	/	14.00/1.5	7300	475	1350	445	25.5
20.5-25	16	/	/	17.00/2.0	8250	350	1490	520	28.5
20.5-25	20	/	/	17.00/2.0	9500	450	1490	520	28.5
23.5-25	16	/	/	19.50/2.5	9500	300	1615	595	31.5
23.5-25	20	/	/	19.50/2.5	10900	375	1615	595	31.5
26.5-25	28	/	/	22.00/3.0	15500	475	1750	675	40.0
29.5-25	28	/	/	25.00/3.5	17500	425	1875	750	40.0

- Available for loaders and dozers.
- Wide application.
- Wear and puncture resistance.



## LL42 (E-3)

OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
14.00-24	16	/	/	10.0	4000	375	1370	375	37.0
14.00-24	24	/	/	10.0	5150	575	1370	375	37.0
14.00-25	28	/	/	10.0	10000/5600	525/650	1370	375	27.0
14.00-25	36	/	/	10.0	11050/5500	1100/850	1370	375	27.0

- Available for large self-dumping trucks, loaders and road graders.
- Wear resistance, good grip and self-cleaning performance.



## LL136 (E-3/L-3)

OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
23.5-25	16	/	/	19.50/2.5	9500	300	1615	595	31.5

- Specialized pattern for sand and other soft surfaces.
- High side-skid resistance and traction.
- Excellence in self-cleaning ability, handling stability and comfort.
- Larger contact area offers even wear and long life.



## LL90 (E-4)

OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
18.00-33	32	/	/	13.00	17500	750	1877	495	50.0
18.00-33	40	/	/	13.00	20000	950	1877	495	50.0

- Available for mobile cranes.
- Stable driving and high loading property.



## LL56 (E-3)

OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
18.00-25	32	/	/	13.00/2.5	8750	575	1615	500	30.0
18.00-25	36	/	/	13.00/2.5	9250	625	1615	500	30.0

- Available for mobile cranes.
- Stable driving and high loading property, excellent wear resistance.



## E-3/L-3

OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
29.5-29	28	/	/	25.00/3.5	19000	425	1975	750	40.0

- Suitable for heavy loaders used on bad road conditions of mine, stone pit and tunnel, etc.
- Good impale and wear resistance.



**E2/L2**  
OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
16.5-25	12	/	/	12.00/1.3	5600	400	1275	395	24.0
17.5-25	12	/	/	14.00/1.5	6150	350	1350	445	25.5
17.5-25	16	/	/	14.00/1.5	7300	475	1350	445	25.5
20.5-25	16	/	/	17.00/2.0	8250	350	1490	520	30.0
20.5-25	20	/	/	17.00/2.0	9500	450	1490	520	30.0
23.5-25	16	/	/	19.50/2.5	9500	300	1615	595	31.5
23.5-25	20	/	/	19.50/2.5	10900	375	1615	595	31.5

- Good steer and traction.
- Off-road pattern has self-cleaning performance and comfort.



**E-4**  
OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
21.00-33	32	/	/	15.00/3.0	10300	500	1940	570	42.0

- Suitable for heavy loaders used on bad road conditions of mine, stone pit and tunnel, etc.
- Good impale and wear resistance.



**E-4**  
OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
21.00-35	32	/	/	15.00/3.0	12150	500	2005	570	42.0
21.00-35	36	/	/	15.00/3.0	12850	550	2005	570	42.0
21.00-35	40	/	/	15.00/3.0	14000	625	2005	570	42.0

- Suitable for heavy loaders used on bad road conditions of mine, stone pit and tunnel, etc.
- Good impale and wear resistance.



**G-2**  
OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
13.00-24	12	/	/	8.00TG	2725	300	1280	335	24.0
13.00-24	18	/	/	8.00TG	3500	450	1280	335	24.0
14.00-24	12	/	/	8.00TG	3075	275	1350	360	24.0
14.00-24	16	/	/	8.00TG	3650	350	1350	360	24.0

- Good steer and traction.
- Off-road pattern has self-cleaning performance and comfort.



**LL55**  
OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
16/70-20	10	/	/	13	2400	250	1075	410	20.0
16/70-20	14	/	/	13	5150	450	1075	410	20.0

- Available for loaders and dozers.
- Wear and puncture resistance.
- Wide application.



**LSM401**  
OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10.00-20	14	/	/	7.5	3260	670	1073	278	/

- Available for loaders operating under seriously tough service conditions in tunnels.
- Excellent wear and cut resistance.
- Flat and smooth tread improves the puncture resistance to stone.



**LL66A**  
OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50-16	14	/	/	6.00G	2390	700	810	215	/
12.00-24	16	/	/	8.5	6150	575	1245	315	/
12.00-24	18	/	/	8.5	6500	750	1245	315	/
12.00-24	20	/	/	8.5	6900	825	1245	315	/

- Available for loaders operating under seriously tough service conditions in tunnels.
- Excellent wear and cut resistance.
- Flat and smooth tread improves the puncture resistance to stone.



**LL66B**  
OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
9.00-20	14	/	/	7.0	4375	725	1015	255	/

- Available for loaders operating under seriously tough service conditions in tunnels.
- Excellent wear and cut resistance.
- Flat and smooth tread improves the puncture resistance to stone.



## LG201 (G-2)

OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
16.00-24	12	/	/	11.25/2.5	3650	225	430	1490	28.5
16.00-24	16	/	/	11.25/2.5	4500	250	430	1490	28.5
16.00-24	20	/	/	11.25/2.5	5450	420	430	1490	28.5

- Good steer and traction.
- Off-road pattern has self-cleaning performance and comfort.



## LL200

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
9.00-15	8	/	/	5.50F	945	245	840	235	8.0
9.00-16	8	/	/	6.50H	985	245	890	245	8.0
14.00-20	20	/	/	10.00V	2635	345	1220	375	8.5

- Available for gravel road.
- Good delivery performance.
- Low rolling resistance and good heat dissipation.
- Lateral grip and high speed performance.



## LL131 (E-3)

OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
13.00-25	28	/	/	8.50	4800	710	1300	335	24.5

- Available for large self-dumping trucks, loaders and road graders.
- Wear resistance, good grip and self-cleaning performance.



## E-3

OTR Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
18.00-25	32	/	/	13.00/2.5	8750	575	1615	500	30.0
18.00-25	40	/	/	13.00/2.5	9750	700	1616	500	30.0

- Available for mobile cranes.
- Stable driving and high loading property.



## LL711

Logging Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
12.00-24	20	/	/	8.5	4495	750	1275	315	36.0

- Available for logging transport of short haul.
- Good running stability and powerful grip.
- Powerful resistance to wear, cut and attack.
- Good traction performance.



# Industrial Tire



**LF401**

Industrial Tire



Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
28X9-15NHS(8.15-15)	14	/	/	7.0	3050	970	710	220	18.0
6.50-10NHS	10	/	/	5.00F	1655	790	590	175	16.0
300-15NHS	18	/	/	8.0	5530	830	840	300	23.5

- High wear resistance and longer life.
- Optimized patterns prevent clamping pebble.



**LL39**

Industrial Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
18×7-8NHS	16	/	/	4.33R	1640	1000	465	173	16.0
6.50-10NHS	10	/	/	5.00F	1655	790	590	175	15.0
6.50-10NHS	14	/	/	5.00F	1975	1070	590	175	15.0
7.00-15NHS	12	/	/	5.50S	2900	850	735	194	20.0
8.15-15NHS	12	/	/	7.0	3230	840	704	215	16.0
28×9-15NHS	12	/	/	7.0	3035	700	710	220	13.0
28×9-15NHS	14	/	/	7.0	3050	970	710	220	13.0

- Good wear and crack resistance.
- Lateral grip.



**LL45**

Industrial Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.00-8NHS	6	/	/	3.50D	850	600	470	137	12.0
5.00-8NHS	10	/	/	3.50D	1150	1000	470	137	12.0
6.00-9NHS	10	/	/	4.00E	1505	860	540	160	10.0
6.50-10NHS	10	/	/	5.00F	1655	790	590	175	15.0
7.00-9NHS	10	/	/	5.00S	1995	860	590	190	12.0
7.00-12NHS	12	/	/	5.00S	2375	860	676	190	12.0
7.50-15NHS	14	/	/	6.0	3375	925	780	215	18.0
8.25-12NHS	12	/	/	6.5	3060	720	765	235	12.0
8.25-15NHS	14	/	/	6.5	3775	830	840	235	15.0
8.25-15NHS	18	/	/	6.5	4240	1000	840	235	15.0
9.00-16NHS	14	/	/	6.50H	4495	760	890	255	16.0

- Wear resistance and lateral grip.
- Stable performance.



**LL65**  
Industrial Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10.00-15NHS	14	/	/	7.5	2800	750	935	280	12.0

- Wear and crack resistance.
- Lateral grip.



**LL102**  
Industrial Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10-16.5NHS	10	/	/	8.25	2135	520	773	264	13.0
10-16.5NHS	12	/	/	8.25	2375	620	773	264	13.0
12-16.5NHS	12	/	/	9.75	2865	550	831	307	13.0

- Wear and crack resistance.
- Low rolling resistance.
- Good heat dissipation.



**LL103**  
Industrial Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
12-16.5LT	10	/	/	9.75	D1418 S1614	420	831	307	13.0
12-16.5LT	12	/	/	9.75	D1650 S1850	520	831	307	13.0

- Wear and crack resistance.
- Good heat dissipation.
- Low rolling resistance.



**LL239**  
Industrial Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
28x9-15NHS	14	/	/	7.0	3050	970	840	235	17.5

- Good wear and crack resistance.
- Lateral grip.



**LL2**  
Industrial Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
9.00-16NHS	14	/	/	6.50H	4080	750	890	255	12.5
9.00-16NHS	14	/	/	6.50H	2635	750	890	255	12.5

- Good wear and crack resistance.
- Lateral grip.



**LBI301**  
Agricultural Tire



Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
600/50-22.5 IMP	16	169	A6	AG20.00	5770	260	1172	611	25.0

- High load capacity.
- Low soil compaction.
- Good traction and self-cleaning performance.

# Agricultural Tire



**LBR102**  
Agricultural Tire



Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
14.9-28	8	/	/	W13	1880	180	1365	378	37.0

- Optimized patterns provide great wear resistance performance.
- Excellent traction performance.



**LL2**  
Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.00-8	4	/	/	3.00D	180	340	425	110	6.5
4.00-8	6	/	/	3.00D	410	420	425	110	6.5
4.00-8	8	/	/	3.00D	700	530	425	110	6.5
4.00-12	6	/	/	3.00D	240	360	535	112	7.5
4.00-14	6	/	/	3.00D	350	400	590	112	8.0
7.00-16	10	/	/	5.50F	1100	530	775	200	12.0
7.00-16	12	/	/	5.50F	1220	530	775	200	12.0
7.00-16	14	/	/	5.50F	1320	730	775	200	12.0

- Wear and crack resistance.
- Lateral grip.





**LL11**  
Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.50-16	10	/	/	5.50F	975	530	750	185	10.0
6.50-16	12	/	/	5.50F	1060	630	750	185	10.0
7.00-16	10	/	/	5.50F	1100	530	775	200	12.0
7.00-16	12	/	/	5.50F	1220	630	775	200	12.0
7.00-16	14	/	/	5.50F	1320	730	775	200	12.0

- Low rolling resistance.
- Good wear and crack resistance.
- Good heat dissipation.



**LL14**  
Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.00-16	8	/	/	3.00D	1200	600	655	130	8.0
5.00-16	10	/	/	3.00D	1350	650	655	130	8.0
6.50-16	10	/	/	5.50F	975	530	760	185	10.5
6.50-16	12	/	/	5.50F	1060	630	750	185	10.5

- Wear resistance and lateral grip.
- Multiple functions.



**LL15**  
Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.00-16	6	/	/	3.00D	800	400	640	110	8.0
6.00-16	6	/	/	4.50E	635	320	730	170	9.0
6.00-16	8	/	/	4.50E	735	420	730	170	9.0
6.00-16	10	/	/	4.50E	860	530	730	170	9.0
6.50-16	10	/	/	5.50F	975	530	750	185	10.0
6.50-16	12	/	/	5.50F	1060	630	750	185	10.0
7.50-16	14	/	/	6.00G	1500	730	805	215	13.0

- Wear and crack resistance.
- Lateral grip.



**LL17**  
Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.50-14	8	/	/	3.00D	1000	450	602	120	8.0

- Low rolling resistance.
- Wear and crack resistance.
- Good heat dissipation.



**LL19**  
Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.50-14	8	/	/	3.00D	595	390	635	158	9.0

- Low noise.
- Fuel saving.
- Good wear resistance.
- Good heat dissipation.



**LL27**  
Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.50-14	8	/	/	3.00D	1000	450	602	120	8.0
5.50-16	8	/	/	4.00E	1100	470	685	150	8.0
5.50-16	10	/	/	4.00E	1325	530	685	150	8.0

- Multiple functions.



**LL21**  
Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.50-12	8	/	/	3.00B	415	400	545	127	7.0

- Low rolling resistance.
- Wear and crack resistance.
- Good heat dissipation.



**LL29**  
Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.50-16	6	/	/	3.00D	615	360	655	122	8.0
4.50-16	8	/	/	3.00D	1000	450	655	122	8.0
4.50-16	10	/	/	3.00D	1325	530	655	122	8.0
5.00-14	8	/	/	3.00D	1200	530	628	130	8.0

- Multiple functions.



## LL31 (R-1)

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.00-12	4	/	/	4.00E	280	200	590	145	22.0
5.50-17	6	/	/	4.00E	440	250	750	145	22.0
6.00-12	4	/	/	4.50E	335	180	640	165	22.0
6.00-12	6	/	/	4.50E	405	250	640	165	22.0
6.00-12	8	/	/	4.50E	420	260	640	165	22.0
6.00-14	6	/	/	4.50E	450	250	690	165	20.5
6.00-14	8	/	/	4.50E	685	420	690	165	20.5
6.00-16	6	/	/	4.50E	495	250	745	165	22.0
7.50-16	6	/	/	5.50F	650	210	810	205	23.0
7.50-16	8	/	/	5.50F	700	240	810	205	23.0
7.50-20	6	/	/	5.50F	760	210	910	205	24.0
7.50-20	8	/	/	5.50F	880	280	910	205	24.0
8.3-24	6	/	/	W7	810	240	995	210	30.0
8.3-24	8	/	/	W7	920	280	995	210	30.0
8.5-20	8	/	/	W7	880	250	895	210	30.0
9.5-20	8	/	/	W8	955	280	950	240	30.0
9.5-24	6	/	/	W8	940	210	1050	240	30.0
9.5-24	8	/	/	W8	1110	280	1050	240	30.0
10-15	8	/	/	9.00	950	310	775	254	20.0
11.2-24	6	/	/	W10	950	180	1105	285	35.0
11.2-24	8	/	/	W10	1150	250	1105	285	35.0
12-38	8	/	/	DW11	1570	140	1575	330	35.0
12.4/11-28	6	/	/	W11	1275	170	1260	315	38.0
12.4/11-28	8	/	/	W11	1510	230	1260	315	38.0
14.9-24	6	/	/	W13	1510	140	1265	378	38.0
14.9-24	8	/	/	W13	1760	180	1265	378	38.0
14.9-28	6	/	/	W13	1610	140	1365	378	38.0
14.9-28	8	/	/	W13	1880	180	1365	378	38.0
16.9-34	8	/	/	W15L	2380	170	1585	430	37.0
16.9-34	10	/	/	W15L	2605	200	1585	430	37.0

- Wear and puncture resistance.
- Good grip and self-cleaning performance.



## LL30

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.00-12	6	/	/	3.00D	240	360	535	110	10.0
4.00-14	4	/	/	3.00D	270	340	590	110	10.0
4.00-14	6	/	/	3.00D	350	400	590	110	10.0
4.00-16	6	/	/	3.00D	800	400	640	110	10.0
4.50-14	8	/	/	3.00D	1000	450	602	120	10.0
4.50-16	6	/	/	3.00D	615	360	655	122	10.0
4.50-16	8	/	/	3.00D	1000	450	655	122	10.0
5.00-14	8	/	/	3.00D	500	450	620	130	12.0
5.00-15	8	/	/	4.00E	675	450	640	130	10.0
6.00-16	6	/	/	4.50E	495	250	745	165	13.0
6.50-20	8	/	/	5.00F	865	420	860	180	16.0

- Lateral grip and wear resistance.
- Good traction performance.



## LL32

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
5.50-16	10	/	/	4.00E	1325	530	715	150	16.0
6.00-16	6	/	/	4.50E	495	250	730	170	18.0
6.00-16	10	/	/	4.50E	755	420	730	170	18.0
6.50-16	10	/	/	5.00F	635	300	765	180	18.0
6.50-16	14	/	/	5.00F	815	460	765	180	18.0
7.00-16	14	/	/	5.50F	1010	460	785	190	18.0
7.50-16	10	/	/	5.50F	800	320	810	205	20.0
7.50-16	14	/	/	5.50F	1030	460	810	205	20.0

- Wear and puncture resistance.
- Good grip and self-cleaning performance.



## LL37 (R-1)

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50-20	6	/	/	5.50F	760	210	910	205	24.0
7.50-20	6	/	/	5.50F	880	280	910	205	24.0

- Wear and puncture resistance.
- Good grip performance.



## LL38

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.50-16	6	/	/	3.00D	615	360	655	122	0.0
4.50-16	8	/	/	3.00D	1000	450	655	122	8.0
4.50-16	10	/	/	3.00D	1325	530	655	122	8.0
5.00-16	8	/	/	4.00E	1200	600	680	135	8.0
5.00-16	10	/	/	4.00E	1350	650	680	135	8.0
5.50-16	8	/	/	4.00E	1100	470	685	150	8.0
5.50-16	10	/	/	4.00E	1325	530	685	150	8.0

- Wear and puncture resistance.
- Lateral grip.



## LL40

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
10-15	8	/	/	9.00	1240	300	752	272	10.0

- Wear and puncture resistance.
- Good traction.



## LL46 (R-1)

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
15-24	10	/	/	DW14	2800	280	1330	410	33.0
16.9-28	8	/	/	W15L	2175	170	1435	430	39.0
16.9-30	8	/	/	W15L	2245	170	1485	430	39.0
16.9-30	10	/	/	W15L	2455	200	1485	430	39.0

- Wear and puncture resistance.
- Good grip and traction performance.



## LL71 (R-2)

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
19.5L-24	10	/	/	17.00	2800	170	1382	495	92.0
28L-26	14	/	/	DW25	4245	170	1672	715	100.0

- Wear and puncture resistance.
- Good grip and self-cleaning performance.



## R-2

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
23.1-26	12	/	/	DW20	3610	170	1662	587	100.0

- Wear and puncture resistance.
- Good grip and self-cleaning performance.



## LL81 (PR-1)

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
9.5-24	8	/	/	W8	1510	280	1150	240	80.0

- Special for paddy field.



## LL82

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.00-8	6	/	/	3.00D	410	420	425	110	6.5
4.00-8	8	/	/	3.00D	700	530	425	110	6.5

- Wear and puncture resistance.
- Good grip and traction performance.



## LL101 (R-4)

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
16.9-28	12	/	/	W15L	3450	260	1410	429	28.0
19.5L-24	12	/	/	DW16	3450	230	1316	495	30.0

- Wear and puncture resistance.
- Good grip and self-cleaning performance.



## LL76 (R-1)

Agricultural Tire

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max. Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
23.1-26-12PR	12	/	/	DW20	3610	170	1605	587	42.0

- Wear and puncture resistance.
- Good grip and self-cleaning performance.



# Solid Tire for Fork Lifts



**LS604**  
Solid Tire for Fork Lifts



Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
23*10-12	/	/	/	8.00G	4450	/	595	232	20.0
200/50-10	/	/	/	6.50F	2910	/	460	198	15.0

- Used for forklifts running on flat surfaces at low speed.
- Pattern blocks are more artistic.
- Offer safety,maintenance-free performance,wear and puncture resistance and over-load capability.



**LS602**  
Solid Tire for Fork Lifts

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
4.00-8	/	/	/	3.00D	1090	/	423	116	5.0
4.00-8	/	/	/	3.75A	1175	/	423	116	5.0

- Used for forklifts running on flat surfaces at low speed.
- Pattern blocks are more artistic.
- Offer safety,maintenance-free performance,wear and puncture resistance and over-load capability.



**LS601**  
Solid Tire for Fork Lifts

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
6.50-10	/	/	/	5.00F	2715	/	597	156	22.0
7.00-12	/	/	/	5.00S	3105	/	683	168	25.0
7.00-15	/	/	/	5.50S	3700	/	759	204	30.0
18*7-8	/	/	/	4.33R	2430	/	457	145	20.0
28*9-15	/	/	/	7.0	4060	/	706	215	27.0
5.00-8	/	/	/	3.00D	1255	/	469	114	21.0
6.00-9	/	/	/	4.00E	1975	/	545	140	24.0
8.25-15	/	/	/	6.5	5085	/	847	205	32.0

- Used for forklifts running on flat surfaces at low speed.
- Pattern blocks are more artistic.
- Offer safety,maintenance-free performance,wear and puncture resistance and over-load capability.



**LS603**  
Solid Tire for Fork Lifts

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
16*6-8	/	/	/	4.33R	1545	/	418	146	18.0
23*9-10	/	/	/	5.50F	3730	/	595	206	24.0
250-15	/	/	/	7.0	5220	/	735	226	25.0
300-15	/	/	/	8.0	6895	/	838	258	30.0

- Used for forklifts running on flat surfaces at low speed.
- Pattern blocks are more artistic.
- Offer safety,maintenance-free performance,wear and puncture resistance and over-load capability.